

2. Amendments to the claims.

- 1 1. (original) A device for holding a bucket of chum submerged in water, comprising:
- 2 a) a cylindrical containing component having a lower edge and an upper
- 3 edge;
- 4 b) a circular bottom component being permanently attached to said lower
- 5 edge of said cylindrical containing component;
- 6 c) a toroidal sleeve being fixedly located near said upper edge of said
- 7 cylindrical containing component;
- 8 d) a drawstring cooperating with said upper edge of said cylindrical
- 9 containing component and pulling said upper edge closed for captivating
- 10 the bucket of chum held within said device; and
- 11 e) a welting having edges;
- 12 wherein said cylindrical containing component is fabricated out of sheet material;
- 13 wherein said sheet material is rectangular and has an upper edge, a lower edge,
- 14 and two side edges;
- 15 wherein said upper edge of said sheet material is said upper edge of said
- 16 cylindrical containing component;
- 17 wherein said lower edge of said sheet material is said lower edge of said
- 18 cylindrical containing component;
- 19 wherein said sheet material has two side edges that are stitched together;

20 wherein said sheet material has a first plurality of orifices therein for permitting
21 chum matter to passthrough;
22 wherein said sheet material has a second plurality of orifices inline therein for
23 cooperating with said drawstring that is threaded therethrough;
24 wherein said sheet material has a longitudinal area extending between said first
25 plurality of orifices and said second plurality of orifices, fabricates said toroidal
26 sleeve, and has a first longitudinal edge and a second longitudinal edge;
27 wherein said toroidal sleeve is fabricated by attaching said first longitudinal edge
28 of said longitudinal area and said second longitudinal edge of said longitudinal
29 area together;
30 wherein said sheet material is flexible plastic material;
31 wherein said circular bottom component is fabricated out of sheet material having
32 at least one orifice therein for permitting the chum matter to pass through;
33 wherein said circular bottom component has a circumference and is permanently
34 attached by stitching near said circumference thereof and near said lower edge of
35 said cylindrical containing component;
36 wherein said edges of said welting are sewn in between said circumference of said
37 circular bottom component and said lower edge of said cylindrical containing
38 component; and
39 wherein said sheet material is flexible plastic material.